

# TRENCH COVER

**Cemetery - Gas Lines - Telephone - Cable - Public Works**

Made from Fiberglass Composite materials. Light enough to be moved by 2 workers. Only weights 70 lbs., no more than a sheet of dry 3/4" plywood. Not affected by weather: wet, cold, hot or dry. Won't rot. Strong enough to support pedestrian traffic without supports. Easy to get to the job.

Consider this; Plywood must be supported with a sub-frame to carry load over open space. It gets wet becomes heavy and rots. Not a very satisfactory solution. Steel Plate works, however if you don't have a machine on the job to move it, then you've got to hire one. With SVE Trench Cover, the problem is solved.



People dig holes in the ground



And, sometimes they need to cover them.

Standard models come with 2 rope handle on each side and connector holes in each corner. Use ground stakes through the holes to anchor the mat against the wind and connect CAUTION tape to the stakes. Trench Cover is not a Road Plate. Do Not use for vehicle traffic. That's what steel plate is for.

In this demo we have a 4' wide Trench Cover supported on the outside edges by (1) one work stand per side. The work stands are 4" wide at the top and 3' long. The amount of support under this Trench Cover is far less than is required in an actual trench situation. There should be a minimum of 6" of support down the entire length of each of the four sides. In this demonstration with two people standing on the unsupported middle, there is no measurable flexing in the panel. Can even be moved by one person.



The SVE Trench Cover is:

- Not affected by water
- Light enough to easily set in place
- Supports pedestrian traffic
- Does not require machinery to handle
- Quickly pays for itself

Convenient sizes

<u>Model</u>	<u>Size</u>	<u>Weight</u>
4896TC	( 4' X 8' X 1/2" )	62 lbs.
48108TC	( 4' X 9' X 1/2" )	70 lbs.
48120TC	( 4' X 10' X 1/2" )	95 lbs.

Custom Sizes Available



**800.762.8267**  
 sales@trakmats.com  
 www.mudtraks.com

6128-F Brookshire Blvd.  
 Charlotte, NC 28216  
 Fax 704.398.0540

